



Customer No. 31013

Docket No. 100647-03950

DAE
[Signature]

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of : Friend et al.

Confirmation No. 1175

Serial No. : 09/882,464

Art Unit : 1762

Filed : June 14, 2001

Examiner : E. Tsoy

For : **MULTILAYERED POLYMERIC STRUCTURE**

CERTIFICATE OF MAILING

I hereby certify that this correspondence is being deposited on April 29, 2005 with the United States Postal Service as First Class Mail in an envelope addressed to Mail Stop PETITIONS, Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450

Signature: *Silvia Salvadori*
Silvia Salvadori, Reg. No. 48,265
Kramer Levin Naftalis & Frankel LLP

Mail Stop PETITIONS
Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

STATEMENT OF SILVIA SALVADORI, PATENT AGENT
RE: Refusal of Stephen O. Friend to Participate

Sir:

Sir:

1. This Statement accompanies the concurrently filed Request for Reconsideration of Petition Under 37 C.F.R. §1.47(a) (the "Request").
2. This Statement set forth the relevant facts to support the Request submitted herewith.
3. On April 25 and 26, 2005, I contacted Mrs. Barbara DiPaola, the Office Manager of Hyperion Catalysis International, and Robert Hoch, consultant of Hyperion Catalysis International, in a good faith attempt to confirm Mr. Friend's current address.

- Hyperion Catalysis International is the owner of record of the above-identified patent application and a previous employer of Mr. Friend. Their records indicated that the last known address of Mr. Friend was 63 Surrey Lane, Boxwood MA, 01921.
4. On April 26, 2005, I sent via Federal Express a copy of the complete application (specification, including claims, drawings, and the unexecuted declaration) of the above-identified patent application, a copy of the unexecuted Assignment to be reviewed and executed by Mr. Friend, and a cover letter transmitting the application papers to the non-signing inventor, as indicated on the copies attached as Exhibit A. I also enclosed a self stamped and self addressed return envelope in the package so that the executed documents could be conveniently returned to us, as indicated on the copy of the Federal Express label attached as Exhibit B.
 5. The documents were delivered to Mr. Friend at his last known address at 63 Surrey Lane, Boxwood MA, 01921. The tracking number Federal Express for this package was 852469260416, as indicated on the copy of the Federal Express Label attached as Exhibit C.
 6. On April 28, 2005, I printed the status of the package from the Federal Express website and I noticed that at 8:30 AM of April 27, 2005, the package had reached Mr. Friend's last known address, which resulted to be an incorrect address. The Federal Express Status reprint is attached as Exhibit D.
 7. On April 28, 2005, a Federal Express package containing a copy of the complete application (specification, including claims, drawings, and the declaration), the assignment and the accompanying cover letter addressed to Mr. Friend was returned to me as undeliverable to Mr. Stephen O. Friend at 63 Surrey Lane, Boxwood, MA 01921, as indicated on the Federal Express label attached as Exhibit E.


8. On April 28, 2005, I telephoned the Friend household at his last known telephone number: (978) 887-0399 at 10.45 AM (EST). The number is no longer in service and no further information was available. In addition, a last attempt to locate Mr. Friend based on a web based search also resulted ineffective, as indicated by the copies of the webpages attached as Exhibit F.
9. Based on the foregoing facts, I believe that I made a *bona fide* attempt to comply with 37 C.F.R. §1.47 and have provided sufficient proof that a copy of the complete application, including a cover letter transmitting the application papers, was sent to the non-signing inventor for review at his last known address as required under 37 C.F.R. §1.47(a).

Dated: April 29, 2005

Respectfully submitted,

KRAMER LEVIN NAFTALIS & FRANKEL LLP

By: Silvia Salvadori
Barry Evans, Reg. No. 22,802
Silvia Salvadori, Reg. No. 48,265
Kramer Levin Naftalis & Frankel LLP
1177 Avenue of the Americas
New York, NY 10036
(212) 715-9100



Customer No. 31013

Docket No. 100647-03950

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of : Friend et al.

Confirmation No. 1175

Serial No. : 09/882,464

Art Unit : 1762

Filed : June 14, 2001

Examiner : E. Tsoy

For : **MULTILAYERED POLYMERIC STRUCTURE**

CERTIFICATE OF MAILING

I hereby certify that this correspondence is being deposited on April 29, 2005, with the United States Postal Service as First Class Mail in an envelope addressed to Mail Stop PETITIONS, Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450

Signature: Silvia Salvadori
Silvia Salvadori, Reg. No. 48,265
Kramer Levin Naftalis & Frankel LLP

Mail Stop PETITIONS
Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

REQUEST FOR RECONSIDERATION OF PETITION UNDER 37 C.F.R. § 1.47

Sir:

Pursuant to 37 C.F.R. §1.47(a) and MPEP §409.03(d), Applicants hereby request reconsideration of the March 29, 2005 Decision Refusing Status Under 37 C.F.R. §1.47(a) ("March 29, 2005 Decision") in the above-identified patent application's Petition to Proceed Without Inventor Participation Under 37 C.F.R. §1.47(a), (the "37 C.F.R. §1.47(a) Petition") filed January 3, 2002.

Applicants' 37 C.F.R. §1.47(a) Petition was dismissed for failure to purportedly provide sufficient proof that a copy of the complete application (specification, including claims,

drawings, and a declaration in compliance with 35 U.S.C. §§ 115 and 116) was sent to the non-signing inventor. The evidence presented with the 37 C.F.R. §1.47(a) Petition appeared to demonstrate that the non-signing inventor was only presented with a declaration. Rather, the March 29, 2005 Decision required that Applicants provide proof that a copy of the application papers (specification, claims and drawings) and an oath or declaration in compliance with 37 C.F.R. §§ 1.63 and 1.64 were sent to Mr. Friend.

Applicants thank the Petitions Attorney Tannouse for confirming that the provisions of 37 C.F.R. §1.47(a) may be satisfied by proof that the relevant materials were sent again to Mr. Friend in compliance with the March 29, 2005 Decision.

Accordingly, Applicants hereby submit: (a) proof that a copy of the complete application (specification, including claims, drawings), a declaration in compliance with 37 C.F.R. §§ 1.63 and 1.64, and an unexecuted assignment were sent to the non-signing inventor for review, (b) a copy of the cover letter transmitting the application papers to the non-signing inventor; and (c) an affidavit by the undersigned, providing first hand details of the efforts made to reach the non-signing inventor.

Thus, Applicants assert that, in addition to the evidence previously submitted, the evidence provided herewith in the exhibits are sufficient to prove the unavailability of the inventor as set forth in 37 C.F.R. §1.47(a), and that the Applicants should be permitted to prosecute the application in the absence of Mr. Stephen O. Friend's signature on the declaration.

Customer No. 31013

Docket No. 100647-03950

Enclosed please find a check for \$ 200.00 to cover the petition fee as set forth in 37 C.F.R. §1.17(g). If there are any additional fees, please charge them to our firm deposit Account No. 50-0540. A second copy of this Request for Consideration is provided herewith.

Dated: April 29, 2005

Respectfully submitted,

KRAMER LEVIN NAFTALIS & FRANKEL LLP

By: Silvia Salvadori
Barry Evans, Reg. No. 22,802
Silvia Salvadori, Reg. No. 48,265
Kramer Levin Naftalis & Frankel LLP
1177 Avenue of the Americas
New York, NY 10036
(212) 715-9100

KRAMER LEVIN NAFTALIS & FRANKEL LLP

April 26, 2005

BY FEDERAL EXPRESS

Mr. Stephen O. Friend
63 Surrey Lane
Boxwood, MA 01921

Re Patent Application of : Stephen O. Friend et al.
Entitled : MULTILAYERED POLYMERIC STRUCTURE
Filed : June 14, 2001
Serial No. : 09/882,464
Our Reference No. : 100647-03950

Re Patent Application of : Stephen O. Friend et al.
Entitled : MULTILAYERED POLYMERIC STRUCTURE
Filed : November 15, 2004
Serial No. : 10/164,682
Our Reference No. : 100647-03960

Dear Mr. Friend:

Further to our communications of November 12, 2001 and April 13, 2005, enclosed please find again a copy of Application Serial No. 09/882,464, an Assignment, and a third copy of the Declaration and Power of Attorney for your execution. Application Serial No. 10/164,682 is a continuation of the Application Serial No. 09/882,464, the Assignment and the Declaration and Power of Attorney of which are enclosed herewith.

Please review the Application, execute the Declaration and Power of Attorney and the Assignment in the appropriate place, and indicate the date of execution next to your signature.

Please then return the executed Declaration and Power of Attorney and the executed Assignment to us no later than April 29, 2005 in the self-addressed stamped Fedex envelope.

KRAMER LEVIN NAFTALIS & FRANKEL LLP

Mr. Stephen O. Friend

April 26, 2005

Page 2

If you have any questions, please do not hesitate to contact me.

Sincerely,



Silvia Salvadori

Patent Agent

Enclosures:

Patent Application (specification with claims and drawings)

Declaration and Power of Attorney

Assignment

Kramer Levin Naftalis & Frankel LLP
File No.: 100647-03950
Serial No.: 09/882,464
Filing Date: June 14, 2001

ASSIGNMENT

We, *Stephen O. Friend* residing at 63 Surrey Lane, Boxwood, MA 01921; *Edward W.S. Bryant*, residing at 5839 E. Wetlands Dr., Longmont, CO 80504; and *Harold C. Fowler*, residing at 2606 Abbott Road, Apt. D-12, Midland, MI 48642; respectively have made certain inventions or discoveries (or both) set forth in an application for Letters Patent of the United States of America entitled: **MULTILAYERED POLYMERIC STRUCTURE**, which application was executed by us and **HYPERION CATALYSIS INTERNATIONAL, INC.**, whose address is 38 Smith Place Cambridge, MA 02138, and which, together with its successors and assigns is hereinafter called "Assignee," is desirous of acquiring the title, rights, benefits and privileges hereinafter recited, and of confirming the same or any part thereof heretofore acquired by Assignee.

Now, therefore, for valuable consideration furnished by Assignee to us, receipt and sufficiency of which we hereby acknowledge, we hereby, without reservation:

1. Assign and convey to and confirm in Assignee the entire right, title and interest in and to said inventions and discoveries, said application for Letters Patent of the United States of America, any and all other applications for Letters Patent on said inventions and discoveries in whatsoever countries, including all divisional, renewal, substitute, continuation and Convention applications based in whole or in part upon said inventions or discoveries or upon said applications, and any and all Letters Patent and reissues and extensions of Letters Patent granted for said inventions and discoveries or upon said applications, and every priority right that is or may be predicated upon or arise from said inventions, said discoveries, said applications and said Letters Patent;

2. Authorize Assignee to file patent applications in any or all countries on any or all of said inventions and discoveries in our names or in the name of Assignee or otherwise as Assignee may deem advisable, under the International Convention or otherwise;

3. Authorize and request the empowered officials of all governments to issue or transfer all said Letters Patent to Assignee, as assignee of the entire right, title and interest therein or otherwise as Assignee may direct;

4. Warrant that we have not knowingly conveyed to others any right in said inventions, discoveries, applications or patents or any license to use the same or to make, use or sell anything embodying or utilizing any of said inventions or discoveries; and that we have good right to assign the same to Assignee without encumbrance;

5. Bind our heirs and legal representatives, as well as ourselves to do, upon Assignee's request and at its expense, but without additional consideration to us or them, all acts reasonably serving to assure that the said inventions and discoveries, the said patent applications and the said Letters Patent shall be held and enjoyed by Assignee as fully and entirely as the same could have been held and enjoyed by us or our heirs or representatives if this assignment had not been made; and particularly to execute and deliver to Assignee all lawful application documents including petitions, specifications, and oaths, and all assignments, disclaimers, and lawful affidavits in form and substance as may be requested by Assignee; to communicate to Assignee all facts known to us relating to said inventions and discoveries or the history

Kramer Levin Naftalis & Frankel LLP
File No.: 100647-03950
Serial No.: 09/882,464
Filing Date: June 14, 2001

Harold C. Fowler

State of)
) ss.:
County of)

On this _____ day of November, 2001 before me
appeared Harold C. Fowler, to me known and known to me to be
the person described in and who executed the foregoing instrument
and he acknowledged the same to be his free act and deed.

Notary Public

(OFFICIAL SEAL)

**IN THE UNITED STATES PATENT AND TRADEMARK OFFICE
APPLICATION FOR LETTERS PATENT**

Inventor(s): Steven O. Friend, Edward W.S. Bryant, Harold C. Fowler

Title: **MULTILAYERED POLYMERIC STRUCTURE**

Specification:

Claims:

Abstract:

Figures:

EXPRESS MAIL

Mailing Label Number EL549007569US

Date of Deposit June 14, 2001

I hereby certify that this paper or fee is being
deposited with the United States Postal Service
"Express Mail Post Office to Addressee" Service
under 37 CFR 1.10 on the date indicated above and
is addressed to the Assistant Commissioner for
Patents, Washington, D.C. 20231

Phyllis Hirschorn

Barry Evans
Registration No. 22,802
KRAMER LEVIN NAFTALIS and FRANKEL LLP
919 Third Avenue
New York, New York 10022
(212) 715-7609

MULTILAYERED POLYMERIC STRUCTURE

This application is a continuation in part of Serial No. 09/593,781 filed June 14, 2000, which is incorporated by reference herein in its entirety.

BACKGROUND OF THE INVENTION

5

Field of Invention

The invention relates generally to electrically conductive polymers and more particularly to antistatic and electrically protective packaging made of multilayered polymeric materials.

Description of the Related Art

10

Antistatic materials

15

The sudden discharge of static electricity which may build on a sensitive electrical component often results in current flow through the component far exceeding its current carrying capacity. In order to protect and avoid the damage or destruction of such components, slow dissipation of the static charge from these components is crucial. For this reason, static-sensitive components are typically transported and stored on trays or in containers made of "antistatic" material having a very high resistance. The high resistance of the material allows electric charge to flow through the material only at very low current levels.

20

Static charges can also impact the quality of signals carried in cables. Static charges can induce or modify electrical fields affecting nearby electrical signals. Antistatic layers can be incorporated into signal cables to minimize effects of nearby static charges.

25

Antistatic materials used to transport or store static sensitive components are generally characterized by a uniform electrically conductive surface having resistance in the range of 1×10^6 to 1×10^{10} ohms per square. Although polymers are generally nonconductive, sheets of polymeric compositions containing conductive impurities or

additives may be made to conduct electricity, and may be used as antistatic materials. The additives discussed include but are not limited to metallic powders, metallic fibers, ionic conductive polymers, intrinsically conductive polymeric powder (e.g., polypyrrole), carbon fibers or carbon black.

5 Although prior art packages and trays made of polymeric material are suitable for dissipating electric charge from sensitive components, they do not protect the components from electric charge originating outside of the tray or package. If a conventional tray or package of the prior art comes in contact with a current source having sufficiently high voltage, electric current can flow through the tray or package,
10 and through the components therein, damaging the components. Trays and packages made from the single layer polymeric materials of the prior art provide no means for shunting current away from the components, and therefor are not suitable for protecting components against charge emanating outside the tray or package. Further, the effectiveness of single layer materials of the prior art may be limited to specific ranges of
15 voltage or frequency.

Carbon Nanotubes

 This invention lies in the field of submicron graphitic carbon fibrils, sometimes called vapor grown carbon fibers or nanotubes. Carbon fibrils are vermicular carbon deposits having diameters less than 1.0μ , preferably less than 0.5μ , and even more
20 preferably less than 0.2μ . They exist in a variety of forms and have been prepared through the catalytic decomposition of various carbon-containing gases at metal surfaces. Such vermicular carbon deposits have been observed almost since the advent of electron microscopy. (Baker and Harris, Chemistry and Physics of Carbon, Walker and Thrower ed., Vol. 14, 1978, p. 83; Rodriguez, N., J. Mater. Research, Vol. 8, p. 3233 (1993)).

25 In 1976, Endo et al. (see Oberlin, A. and Endo, M., J. of Crystal Growth, Vol. 32 (1976), pp. 335-349), hereby incorporated by reference, elucidated the basic mechanism by which such carbon fibrils grow. They were seen to originate from a metal catalyst particle, which, in the presence of a hydrocarbon containing gas, becomes supersaturated

in carbon. A cylindrical ordered graphitic core is extruded which immediately, according to Endo et al., becomes coated with an outer layer of pyrolytically deposited graphite. These fibrils with a pyrolytic overcoat typically have diameters in excess of 0.1μ , more typically 0.2 to 0.5μ .

5 In 1983, Tennent, U.S. Patent No. 4,663,230, hereby incorporated by reference, describes carbon fibrils that are free of a continuous thermal carbon overcoat and have multiple graphitic outer layers that are substantially parallel to the fibril axis. As such they may be characterized as having their cylindrical axes, the axes which are perpendicular to the tangents of the curved layers of graphite, substantially perpendicular
10 to their cylindrical axes. They generally have diameters no greater than 0.1μ and length to diameter ratios of at least 5. Desirably they are substantially free of a continuous thermal carbon overcoat, i.e., pyrolytically deposited carbon resulting from thermal cracking of the gas feed used to prepare them. Thus, the Tennent invention provided access to smaller diameter fibrils, typically 35 to 700\AA (0.0035 to 0.070μ) and to an
15 ordered, "as grown" graphitic surface. Fibrillar carbons of less perfect structure, but also without a pyrolytic carbon outer layer have also been grown.

The carbon nanotubes which can be oxidized as taught in this application, are distinguishable from commercially available continuous carbon fibers. In contrast to these fibers which have aspect ratios (L/D) of at least 10^4 and often 10^6 or more, carbon
20 fibrils have desirably large, but unavoidably finite, aspect ratios. The diameter of continuous fibers is also far larger than that of fibrils, being always $>1.0\mu$ and typically 5 to 7μ .

Tennent, et al., US Patent No. 5,171,560, hereby incorporated by reference, describes carbon fibrils free of thermal overcoat and having graphitic layers substantially
25 parallel to the fibril axes such that the projection of said layers on said fibril axes extends for a distance of at least two fibril diameters. Typically, such fibrils are substantially cylindrical, graphitic nanotubes of substantially constant diameter and comprise cylindrical graphitic sheets whose c-axes are substantially perpendicular to their

cylindrical axis. They are substantially free of pyrolytically deposited carbon, have a diameter less than $0.1\ \mu$ and length to diameter ratio of greater than 5. These fibrils can be oxidized by the methods of the invention.

5 When the projection of the graphitic layers on the nanotube axis extends for a distance of less than two nanotube diameters, the carbon planes of the graphitic nanotube, in cross section, take on a herring bone appearance. These are termed fishbone fibrils. Geus, U.S. Patent No. 4,855,091, hereby incorporated by reference, provides a procedure for preparation of fishbone fibrils substantially free of a pyrolytic overcoat. These carbon nanotubes are also useful in the practice of the invention.

10 Carbon nanotubes of a morphology similar to the catalytically grown fibrils described above have been grown in a high temperature carbon arc (Iijima, Nature, 354, 56, 1991). It is now generally accepted (Weaver, Science, 265, 1994) that these arc-grown nanofibers have the same morphology as the earlier catalytically grown fibrils of Tennent. Arc grown carbon nanofibers after colloquially referred to as "bucky tubes",
15 are also useful in the invention.

Carbon nanotubes differ physically and chemically from continuous carbon fibers which are commercially available as reinforcement materials, and from other forms of carbon such as standard graphite and carbon black. Standard graphite, because of its structure, can undergo oxidation to almost complete saturation. Moreover, carbon black is
20 amorphous carbon generally in the form of spheroidal particles having a graphene structure, carbon layers around a disordered 20 nucleus. The differences make graphite and carbon black poor predictors of nanotube chemistry.

Aggregates of Carbon Nanotubes

As produced carbon nanotubes may be in the form of discrete nanotubes,
25 aggregates of nanotubes or both.

Nanotubes are prepared as aggregates having various morphologies (as determined by scanning electron microscopy) in which they are randomly entangled with

each other to form entangled balls of nanotubes resembling bird nests ("BN"); or as aggregates consisting of bundles of straight to slightly bent or kinked carbon nanotubes having substantially the same relative orientation, and having the appearance of combed yarn ("CY") e.g., the longitudinal axis of each nanotube (despite individual bends or kinks) extends in the same direction as that of the surrounding nanotubes in the bundles; or, as, aggregates consisting of straight to slightly bent or kinked nanotubes which are loosely entangled with each other to form an "open net" ("ON") structure. In open net structures the extent of nanotube entanglement is greater than observed in the combed yarn aggregates (in which the individual nanotubes have substantially the same relative orientation) but less than that of bird nest.

The morphology of the aggregate is controlled by the choice of catalyst support. Spherical supports grow nanotubes in all directions leading to the formation of bird nest aggregates. Combed yarn and open nest aggregates are prepared using supports having one or more readily cleavable planar surfaces, e.g., an iron or iron-containing metal catalyst particle deposited on a support material having one or more readily cleavable surfaces and a surface area of at least 1 square meters per gram. Moy et al., U.S. Application Serial No. 08/469,430 entitled "Improved Methods and Catalysts for the Manufacture of Carbon Fibrils", filed June 6, 1995, hereby incorporated by reference, describes nanotubes prepared as aggregates having various morphologies (as determined by scanning electron microscopy).

Further details regarding the formation of carbon nanotube or nanofiber aggregates may be found in the disclosure of U.S. Patent No. 5,165,909 to Tennent; U.S. Patent No. 5,456,897 to Moy et al.; Snyder et al., U.S. Patent Application Serial No. 07/149,573, filed January 28, 1988, and PCT Application No. US89/00322, filed January 28, 1989 ("Carbon Fibrils") WO 89/07163, and Moy et al., U.S. Patent Application Serial No. 413,837 filed September 28, 1989 and PCT Application No. US90/05498, filed September 27, 1990 ("Battery") WO 91/05089, and U.S. Application No. 08/479,864 to Mandeville et al., filed June 7, 1995 and U.S. Application No. 08/284,917, filed August 2, 1994 and U.S. Application No. 08/320,564, filed October 11, 1994 by Moy et al., all of

which are assigned to the same assignee as the invention here and are hereby incorporated by reference.

OBJECTS OF THE INVENTION

It is therefore an object of the invention to provide an improved packaging
5 material which will protect sensitive electric components from damage or destruction due to electrostatic discharge.

It is a further object of the invention to provide improved packages and carrying trays for electrical components.

It is a further object of the invention to provide improved shielding for
10 signal carrying cables.

SUMMARY OF THE INVENTION

A packaging material is provided having multiple polymeric layers. Each layer comprises a mixture of a polymer and carbon fibrils. The multilayered material has an inner layer with a uniform surface resistance in the range of 1×10^6 ohms per square to
15 1×10^{10} ohms per square, and an outer layer with a surface resistance lower than that of the inner layer. The inner and outer layers may be directly in contact with one another, or there may be intermediate layers of conductive material between them. Each intermediate layer could be made of any material having a surface resistance of at least 10^{10} ohms per square. The surface resistance of the packaging material varies from $10^{0.5}$ to 10^{10} ohms
20 per square, preferably from 10^1 to 10^8 ohms per square.

In a two-layer polymeric structure, the first layer contains a polymer having 0.25% to 25% by weight of carbon fibrils. This concentration of fibrils provides the antistatic layer with a surface resistance in the range of 1×10^6 to 1×10^{10} ohms per square. The second layer may contain 2% to 35% by weight of carbon fibrils, thereby
25 providing a lower resistance relative to the first antistatic layer. Each polymeric layer can have a thickness from about 0.5 mils to about 175 mils and preferably from about 5 mils

to about 30 mils. The entire multilayered polymeric structure can be of whatever thickness is desirable for a given application. For example, the structure of the invention can be from about 1 mil to about 250 mils, preferably from about 2 mils to about 100 mils and most preferably from about 10 mils to about 60 mils.

5 Once each of the polymeric compositions comprising the various layers of the invention are prepared, they are combined to form a composite multilayered material. If the separate layers of polymeric composition are allowed to cure prior to being joined, the combining process consists of applying heat and pressure which causes the separate layers to fuse together. It is, however, preferred that the separate layers of polymeric
10 material are joined prior to curing. This may be accomplished via a coextrusion process, where two or more polymeric compositions are forced through a single aperture. The multilayered material produced by coextrusion may either be allowed to cure as a flat sheet, or may be placed into molds in the form of a desired end-product, i.e. a tray. Each polymeric layer can be processed according to any applicable kind of polymer
15 processing, it being understood that the carbon fibril loading does not limit its processability.

 As used herein to "cure" or "curing" refers to a process of conversion of raw or reactive polymer systems to a finished and useful condition usually by transfer of heat and/or application of chemicals which induce physical and/or chemical changes.
20 Cooling of a molten polymeric composition into a solid layer or sheet is an example of curing. Another example of curing is the process of crosslinking a thermosetting product.

 The polymeric material of the invention may be formed into any one of a number of shapes or configurations suitable for the transport and/or storage of sensitive electrical components, i.e. trays and packages. When the material of this invention is
25 formed into a tray or package, the antistatic layer of the material is situated such that it faces the inside of the tray or package, and comes directly in contact with the component. A more conductive polymeric layer of the material forms the outside surface of the tray or package.

An advantage of having the outer layer of the multilayered material more conductive than the inside antistatic layer is that the outer layer acts as a shunt for any electric current originating outside of a tray or package made of the material. Should a source of electric charge come in contact with the outside surface of a tray or package
5 made of the multilayered material, the outer layer will conduct the current to a point on the outer surface where the current may leave the material. The relatively higher resistance of the inner antistatic layer impedes current flow through that layer and into components which may be present on the other side.

The multilayer materials can be used in other applications where a
10 gradient in electrical properties is desired. Changes in the in concentration of fibrils can lead to changes in both the conductivity and the permittivity of the resulting composite. Other applications include: dielectric lenses made of layers with different levels of carbon fibrils; field limiting insulation layers for cables or electronic parts; and selective shielding or EMI bandpass filters for cables or signal carrying lines.

15 In these examples, the different levels of carbon fibrils in the layers asymmetrically modifies the flow of current or charge perpendicular to the layers or modifies electrical fields.

BRIEF DESCRIPTION OF THE FIGURES

Fig. 1 shows a cross-section of a two layer polymeric material according
20 to the invention.

Fig. 2 shows a tray made from the two layer polymeric material of Fig. 1.

Fig. 3 shows two layers made of polymeric compositions having fibrils therein being combined to form the two layer conductive polymeric material of Fig. 1.

Fig. 4 is a test set-up diagram of a molded tensile bar utilized for measuring DC resistance through the volume of samples in example 1 to 9.

DETAILED DESCRIPTION OF THE INVENTION

In a preferred embodiment of the invention, the material has two layers, as shown in the cross-sectional view of Fig. 1. The polymeric material 1 of the invention is a composite of a first layer 1a and a second layer 1b, each layer being a mixture of carbon fibrils in a polymer. The electrical resistance of each polymeric composition is inversely related to the concentration of fibrils in the composition, i.e., the higher the concentration of fibrils, the lower the electrical resistance of the composition. Therefore, the first layer 1a of polymeric material, with a 2.5% by weight concentration of carbon fibrils, has a surface resistance of about 1×10^7 ohms per square. The second layer 1b, having a fibril concentration of 5.0% has a surface resistance of only about 1×10^4 ohms per square.

Carbon fibrils are typically in the form of vermicular tubes with graphitic outer layers disposed substantially concentrically about the cylindrical axis of the fibril. Preferably, the fibrils are substantially free of a pyrolytically deposited thermal carbon overcoat.

Carbon fibrils have a length-to-diameter ratio of at least 5, and more preferably at least 100. Carbon fibrils are carbon filaments having diameters less than 500 nanometers. Even more preferred are fibrils whose length-to-diameter ratio is at least 1000. The wall thickness of the fibrils is about 0.1 to 0.4 times the fibril external diameter which is preferably between 3.5 and 75 nanometers. In applications where high strength fibrils are needed, e.g., where the fibrils are used as reinforcements, the external fibril diameter is substantially constant over its length.

Generally, preferred classes of polymers used for this invention include thermosets, thermoplastics, elastomers and inorganics. Certain polymeric alloys, defined as two or more miscible or partially miscible polymers, and blends, defined as discrete non-miscible phases, are also preferred. Specific examples of thermosets and elastomers

include polyurethanes, natural rubber, synthetic rubber, epoxy, phenolic, polyesters, polyamides, and silicones. Specific examples of thermoplastics include polyacetal, polyacrylic, acrylonitrile-butadiene-styrene, polycarbonates, polystyrenes, polyethylene, styrene acrylonitrile, polypropylenes, polyethylene terephthalate, polybutylene terephthalate, polyamide (6, 6/6, 6/10, 6/12, 11 or 12), polyamide-imides, polyarylates, polyurethanes, thermoplastic olefins (i.e., polypropylene/impact modifiers such as ethylene, propylene and rubber), thermoplastic elastomers, polyarylsulfone, polyethersulfone, polyphenylene sulfide, polyvinyl chloride, chlorinated polyvinyl chloride, polysulfone, polyetherimide, polytetrafluoro ethylene, fluorinated ethylene propylene, perfluoroalkoxy, polychlorotrifluoro ethylene, ethylene tetrafluoro ethylene, polyvinylidene fluoride, polyvinyl fluoride, polyetherketone, polyether etherketone and polyether ketone ether ketone. Specific examples of alloys and blends include acrylonitrilebutadiene-styrene/polyamide, polycarbonate/acrylonitrile-butadiene-styrene, acrylonitrile butadiene styrene/polyvinyl chloride, polyphenylene ether/polystyrene, polyphenylene ether/polyamide, polysulfone/acrylonitrile-butadiene-styrene, polycarbonate/thermoplastic urethane, polycarbonate/polyethylene terephthalate, thermoplastic elastomer alloys, polyamide/elastomers, polyester/elastomers, polyethylene terephthalate/polybutyl terephthalate, acetal/elastomer, styrene-malefic-anhydride/acrylonitrile-butadiene-styrene, polyether etherketone/polyethersulfone, polyethylene/polyamide and polyethylene/acetal. Specific examples of inorganic polymers include phosphorus based compounds and silicones.

In a preferred embodiment of the invention, the polymer comprises a blend of polymers possessing advantageous properties and a compatibilizer or a compatibilizer with a modifying resin for facilitating the blending of the polymers. Specific examples of such blends include polyphenylene ethers (PPE) or polyphenylene oxides (PPO) with polyamides (e.g., nylons) or polycarboxylic reactants. Examples of such polymer blends with compatibilizers or compatibilizers and modifying agents are described in U.S. Pat. Nos. 4,988,775 and 5,132,365 and in European Patent Application Nos. 90124310.5, 90300841.5, 91112496.4 and 92109100.5.

The polymeric compositions comprising each of the various layers of the multilayered structure of this invention are made by known methods, such as those described in U.S. Pat. Nos. 5,643,502, 5,651,922 and 5,591,382 to Nahass et al. U.S. Patent Nos. 5,591,382; 5,651,922; and 5,643,502 all to Nahass et al. disclose a polymeric composition having improved toughness and conductivity which includes carbon fibrils, at least a portion of which are in the form of aggregates, substantially all of which aggregates are less than 35 μ m in diameter. A method for preparing this polymeric composition is also disclosed. The method includes mixing the carbon fibrils, most of which are in the form of aggregates, with a polymeric material by applying shear to break down the aggregates and distribute them in the polymeric material until substantially all of the aggregates are less than 35 μ m in diameter. The patents to Nahass et al. are incorporated herein by reference as if set forth in full.

One method of combining layers 1a and 1b involves first shaping each of the compositions into individual flat sheets and allowing the sheets to cure. After curing, the sheets are pressed together under conditions of high heat and pressure, causing them to fuse to one another. Conductive adhesives may also be used to join separate sheets of polymeric composition to one another.

Another method is to insert or over-mold the two layers. In this process an injection molding machine is used to mold the first layer. The resultant part is then placed into a second mold where the second layer is then molded onto the first. The heat from the second layer causes a melt-bond to form between the first and second layers. In this way the layers are cured sequentially. The same effect can also be achieved using a special two-shot or multi-shot molding machine. This is an apparatus that has two or more barrels that inject polymeric materials into the same mold. Materials with different conductivities are placed in different barrels and injected into the mold separately to form a two or more layered part.

Once the polymeric compositions constituting each of the layers of the multilayered polymer structure are prepared, they are preferably combined in a coextrusion process as schematically depicted in Fig. 3.

5 In this preferred process, two or more viscous materials are combined into a multilayered product. The polymeric compositions of the first and second layers 1a and 1b are forced through an aperture before either composition has had a chance to cure. This forms a multilayered sheet of polymeric compositions which can be placed in a mold. A similar process can be used to coextrude multilayer tubes or jackets for cables or wires.

10 Fig. 2 shows a tray 3 made from the multilayered material of this invention. The first layer 1a of the material forms the inside antistatic surface of the tray 3. A carbon fibril concentration of 2.5% by weight provides the inside layer with a surface resistance of about 1×10^7 ohms per square. The high level of surface resistance of the inside layer 1a allows for the slow dissipation of any electro-static charge which
15 may build on components present inside the tray 3. This charge is dissipated through the outer layer 1b which is in electrical contact with the inner layer 1a.

The second layer 1b forms the outside surface of the tray 3 and has a surface resistance of about 1×10^4 ohms per square. The second layer contains about 5% by weight of carbon fibrils, and due to the lower resistance of layer 1b relative to 1a,
20 layer 1b reduces the risk of electrical charge flowing from outside the tray into the tray and damaging components therein. Layer 1b acts as a shunt guiding current away from the sensitive components inside the tray. Item 4 in Fig. 2 represents an electrical component which can be carried by using tray 3.

25 The multilayered polymeric material of this invention may be formed into any shape or configuration including trays, packages, boxes, and the like by injection molding, blow molding, RIM, or any other method commonly known for shaping

polymeric materials. The antistatic properties of the packaging material of the invention are measured according to the procedure described in ASTM D-257.

EXAMPLES

The following examples serve to provide further appreciation of the invention but are not meant in any way to restrict the effective scope to the invention.

Examples 1- 9

Masterbatch compositions containing 15% fibril loading were prepared according to methods described in the examples section of U.S. Patent No. 5,651,922 to Nahass et al. incorporated herein by reference. Masterbatch formulations were prepared having 15% by weight carbon fibrils obtained from bird's nest (BN) aggregates and 85% polyethylene terephthalate modified with cyclohexanedimethanol (PETG). Other masterbatch compositions included 15% by weight carbon fibrils from bird's nest type aggregates and 85% polybutylene terephthalate (PBT). Yet other masterbatch composition were prepared to include 15% by weight carbon fibrils from bird's nest type aggregates and 0.5% by weight polytetrafluoroethylene (PTFE) and the balance PETG.

The above masterbatch compositions were used to make other formulations as listed in Table 1 below. For example, to make a PETG/SBN product 33.5% PBT/15BN was mixed with 66.7% PETG polymer. PBT and PETG trans-esterify to form a hybrid mixture of two polymers with a single flow transition temperature and are crystalline in nature. The impact modifier (IM) used in these formulations was rubber. For example, formulation 7 of table 1 contains 2% by weight impact modifier, 5% by weight carbon fibrils from bird's nest aggregates and a hybrid mixture of 28 wt% PBT and 65 wt% PETG. Electrical properties for each formulation, such as volume and surface resistivity were measured and are listed for each formulation in Table 1 below.

Table 1

Example	Formulation	Masterbatch	Volume Resistivity ohm-cm	Surface Resistivity ohm/square
1	PETG/2IM/5BN	PETG/15BN	6.63E+02	2.86E+05
2	PETG/4 IM/5BN	PETG/15BN	5.80E+02	7.71E+06
3	PETG/6 IM/5BN	PETG/15BN	9.30E+02	8.00E+06
4	PETG/2IM/5BN	PETG/0.5PTFE/15BN	2.30E+03	1.90E+06
5	PETG/4IM/5BN	PETG/0.5PTFE/15BN	6.80E+02	3.70E+06
6	PETG/6IM/5BN	PETG/0.5PTFE/15BN	1.40E+02	4.00E+06
7	PETG/2IM/5BN	PBT/15BN	1.00E+02	3.90E+05
8	PETG/4IM/5BN	PBT/15BN	8.74E+02	1.17E+07
9	PETG/6IM/5BN	PBT/15BN	8.46E+02	8.57E+04

DC resistance through the volume of the samples was measured at 2 volts and converted to volume resistivity using the formula shown with the test set-up diagram in Figure 4. Electrodes were painted on each end of injection molded tensile bars with silver conducting paint after cutting away the tabs from each end. The leads of a multi-meter were then contacted with the silver paint electrode strips 2a and 2b on the sample in order to obtain surface resistivity measurements and with the silver paint electrode strips 3a and 3b in order to obtain volume resistivity measurements. In Figure 4, d is the electrode spacing for surface resistivity test, l is the electrode spacing for volume resistivity test, w is the electrode width and t is the sample thickness, all values are measured in centimeters. Based on the foregoing variables, the surface and volume resistivity are calculated as follows:

$$\text{surface resistivity (ohm/square)} = \text{resistance [ohm]} / (d \text{ [cm]} / w \text{ [cm]})$$

$$\text{volume resistivity (ohm-cm)} = \text{resistance [ohm]} \times t \text{ [cm]} / (l \text{ [cm]} / w \text{ [cm]})$$

Discussion of Experimental Results

Any one of the formulations above can be combined with another to form a bilayered polymeric structure useful in forming the packaging material of the present invention. For example, a bilayered polymeric structure can be made by coextrusion or lamination with a conductive adhesive between the layers by overmolding or by two-shot

molding. The resulting bilayered structure is then thermoformed into a tray wherein the layer prepared from composition 1 is the inside layer having the higher surface resistivity.

Although the invention has been described with reference to specific examples, they should not be construed as limiting since they are merely illustrative of the invention. One of skill in the art may alter the described examples without departing from the spirit or scope of the invention

We claim:

1. A multilayered polymeric structure for protecting electronic components comprising at least a first polymeric layer and a second polymeric layer in surface contact with one another, said first and second polymeric layers each containing a different
5 amount of carbon fibrils.
2. The multilayered polymeric structure according to claim 1, wherein said first and said second polymeric layers each comprise from about 0.25% to about 35% by weight of carbon fibrils.
3. The multilayered polymeric structure according to claim 1, wherein said
10 first and said second polymeric layers each comprise from about 1.0% to about 15% by weight of carbon fibrils.
4. The multilayered polymeric structure according to claim 1, wherein said first and said second polymeric layers each comprise from about 2.0% to about 7% by weight of carbon fibrils.
- 15 5. The multilayered polymeric structure according to claim 1, wherein said first polymeric layer comprises from about 0.25% to about 25% by weight of carbon fibrils and said second polymeric layer comprises from about 2% to about 35% by weight of carbon fibrils.
6. The multilayered polymeric structure according to claim 1, further
20 comprising at least an electrically conductive material between said first polymeric layer and said second polymeric layer.
7. The multilayered polymeric structure according to claim 6, wherein the electrically conductive material is an adhesive.
8. The multilayered polymeric structure according to claim 1, wherein the
25 surface resistance in said second polymeric layer is at least one order of magnitude greater than the surface resistance of said first polymeric layer.

9. The multilayered polymeric structure according to claim 1, wherein the surface resistance of each of said polymeric layers is in the range of 1×10^1 ohms per square to 1×10^{12} ohms per square.

10. The multilayered polymeric structure according to claim 9, wherein the surface resistance of said second polymeric layer is in the range of 1×10^1 to 1×10^6 ohms per square.

11. The multilayered polymeric structure according to claim 9, wherein the surface resistance of said first polymeric layer is in the range of 1×10^6 ohms per square to 1×10^{12} ohms per square.

12. A process for making a multilayered polymeric structure for protecting an electronic component which comprises:

(a) forming at least a first polymeric layer and a second polymeric layer, each layer comprising a different amount of carbon fibrils;

(b) combining said first and second polymeric layer to form said multilayered polymeric structure.

13. The process according to claim 12, wherein said first and second polymeric layers comprise from about 0.25% to about 35% by weight of carbon fibrils.

14. The process according to claim 12, wherein said first polymeric layer comprises from 0.25 to 25% by weight carbon fibrils and said second polymeric layer comprises from 2% to 35% by weight carbon fibrils.

15. The process according to claim 12, wherein said layers are combined by coextrusion or lamination, or by two shot or multi-shot injection molding or by insert injection molding.

16. The process according to claim 12, wherein said first polymeric layer has a higher surface resistance than said second polymeric layer.

17. The process according to claim 16, wherein said multilayered polymeric structure is formed into a tray or packaging material, wherein said electronic component is in contact with said first polymeric layer.

18. The process according to claim 16, further comprising forming third
5 polymeric layer in surface contact with said first or said second polymeric layer, said third polymeric layer comprising from about 0.25% to about 35% by weight carbon fibrils.

19. A process for making a bilayered polymeric structure for packaging of electronic components which comprises:

10 (a) forming a first polymeric sheet from a first molten composition comprising a polymer comprising from 0.26% to 25% by weight of carbon fibrils;

(b) forming a second polymeric sheet from a second molten composition comprising a polymer comprising from 2% to 35% by weight of carbon fibrils; and

15 (c) combining said first and second sheet into said bilayered polymeric structure.

20. The process according to claim 19, wherein said layers are combined by lamination or coextrusion, or two shot or multi-shot injection molding or by insert injection molding.

21. The process according to claim 19, wherein said first and second molten compositions are allowed to become cured after step (c) or cured sequentially.

22. The process according to claim 19, further comprising adding a conductive adhesive between said first polymeric sheet and said second polymeric sheet.

23. A container for sensitive electrical components comprising:

(a) a first layer of polymeric material adapted to support an electrical component, said first polymeric layer comprising from about 0.25% to about 25% by weight carbon fibrils and having a resistivity in the range of from about 1×10^5 ohms per square to about 1×10^{12} ohms per square; and

5 (b) a second layer of polymeric material in surface contact with said first layer, said second layer forming the outer layer of said container comprising from about 2% to about 35% by weight carbon fibrils and having a resistivity in the range of from about 1×10^1 ohms per square to about 1×10^6 ohms per square.

24. The container of claim 23, further comprising at least an electrically
10 conductive material between said first polymeric layer and said second polymeric layer.

25. The container of claim 24, wherein the electrically conductive material is an adhesive.

26. The container of claim 23, wherein said first polymeric layer and said second polymeric layer comprise a hybrid mixture of PETG and PBT said mixture
15 comprising from about 0% to about 100% by weight PETG, the remaining portion being PBT.

27. The container of claim 23, further comprising a third polymeric layer in surface contact with said first or said second layer of polymeric material, said third polymeric layer comprising from about 0.25% to about 35% by weight carbon fibrils and
20 having a resistivity in the range from about 1×10^1 ohms per square to about 1×10^1 ohms per square.

28. A protective covering for an electrical current carrying cable comprising:

(a) a first layer of polymeric material adapted to support an electrical component, said first polymeric layer comprising from about 0.25% to about 25% by
25 weight carbon fibrils and having a resistivity in the range of from about 1×10^5 ohms per square to about 1×10^{12} ohms per square; and

(b) a second layer of polymeric material in surface contact with said first layer, said second layer forming the outer layer of said container comprising from about 2% to about 35% by weight carbon fibrils and having a resistivity in the range of from about 1×10^1 ohms per square to about 1×10^6 ohms per square.

ABSTRACT

A multilayered polymeric structure having at least two polymeric layers is provided, each layer being a mixture of a polymeric composition with carbon fibrils. The multilayer polymeric structure may include an electrically conductive material between
5 the first and second polymeric layers. A process for making a multilayered polymeric structure for packaging electronic components is also provided. The multilayered polymeric material is used to form trays and packages for containing electrical components.

1 / 4




FIG. 1

2/4




FIG. 2

3/4




FIG. 3

4/4




FIG. 4

Express

274

400

FedEx. US Airbill
Express

FedEx Tracking Number

8494 0753 4044

1 From 41 105 Sender's FedEx Account Number

Date

Sender's Name MR. STEPHEN FRIEND Phone (978) 887-0399

Company

Address 63 SURREY LANE Dept./Floor/Room

City BOX WOOD State MA ZIP 01921

2 Your Internal Billing Reference

Print or characters not appear on package

3 To Recipient's Name A. B. CHEN Phone (212) 715-9174

Company KRAMER LEVIN NAFTALIS FRANKEL

Recipient's Address 1177 AVENUE OF THE AMERICAS

We cannot deliver to P.O. boxes or F.O. ZIP codes.

Address To request a package be held at a specific FedEx location, print FedEx address here.

City NEW YORK State NY ZIP 10036-2714

Try online shipping at fedex.com

By using this Airbill you agree to the service conditions on the back of this Airbill and in our current Service Guide, including terms that limit our liability.

Questions? Visit our Web site at fedex.com

or call 1.800.GoFedEx 1.800.463.3333

NO POUCH NEEDED
See back for peel and stick application instructions.

PULL AND RETAIN THIS COPY BEFORE AFFIXING TO THE PACKAGE.

Sender's Copy

0215

02111

4a Express Package Service Packages up to 150 lbs. To next location

☒ FedEx Priority Overnight Next business morning ☐ FedEx Standard Overnight Next business afternoon ☐ FedEx First Overnight Earliest next business morning delivery to select locations

☐ FedEx 2Day Second business day ☐ FedEx Express Saver Third business day ☐ FedEx Freight Freight Second business day

4b Express Freight Service Packages over 150 lbs. To next location

☐ FedEx 10day Freight First business day ☐ FedEx 30day Freight Third business day

5 Packaging ☒ FedEx Envelope ☐ FedEx Box ☐ FedEx Tube ☐ Other

6 Special Handling ☐ Saturday Delivery ☐ HOLD Weekday at FedEx Location ☐ HOLD Saturday at FedEx Location ☐ AVAILABLE ONLY for FedEx Priority Overnight, FedEx 2Day, FedEx 10day Freight, and FedEx 30day Freight to select ZIP codes

7 Payment ☒ Recipient ☐ Third Party ☐ Credit Card ☐ Cash/Check

8 Sign to Authorize Delivery Without a Signature

Total Packages 1 Total Weight 0100-2318-1 Total Declared Value \$.00

By signing this Airbill you agree to the service conditions on the back of this Airbill and in our current Service Guide, including terms that limit our liability.

Questions? Visit our Web site at fedex.com

or call 1.800.GoFedEx 1.800.463.3333

0307206828

0307206828

0307206828

0307206828

0307206828

0307206828

0307206828

[United States Home](#)[Information Center](#) | [Custom](#)[Package / Envelope Services](#)[Office / Print Services](#)[Freight Services](#)[Expedited Servi](#)[Ship](#)[Track](#)[Manage My Account](#)[International Tools](#)Track Shipments
Detailed Results[Printable Version](#) [Quick Help](#)

You can also track:

- [By TCN](#)
- [FedEx Track shipments](#)
- [By Email Tr](#)
- [By FedEx V Solutions](#)

Tracking number 852469260416
Ship date Apr 26, 2005Reference 100647/03950
Delivered to Residence
Service type Priority Envelope
Weight 1.0 lbs.

Status Delivery exception

Date/Time	Activity	Location	Details
Apr 27, 2005	5:52 PM Package returned to shipper	PEABODY, MA	Return tracking number: 792908716427
	3:40 PM At local FedEx facility	PEABODY, MA	
	8:30 AM Delivery exception	PEABODY, MA	Incorrect address
	7:58 AM On FedEx vehicle for delivery	PEABODY, MA	
	7:21 AM At local FedEx facility	PEABODY, MA	
	7:06 AM At dest sort facility	EAST BOSTON, MA	
Apr 26, 2005	7:01 AM Departed FedEx location	NEWARK, NJ	
	10:54 PM Arrived at FedEx location	NEWARK, NJ	
	9:44 PM Left origin	NEW YORK, NY	
	8:06 PM Picked up	NEW YORK, NY	

[Wrong Address?](#)
Reduce future mistal
FedEx Address Che[Shipping Freight?](#)
FedEx has LTL, air
surface and air exp
multi piece packagi
and ocean freight.[Signature proof](#)[Track more shipments](#)

Email your detailed tracking results (optional)

Enter your email, submit up to three email addresses (separated by commas), add your message (optional), and click **Send email**.

From

To

Add a message to this email.

[Send email](#)


From: Origin ID: (800)463-3339
service agent returns
FEDEX / GOMA
4 LAKELAND PARK DRIVE
PEABODY, MA 01960



SHIP TO: (212)715-9174 BILL RECIPIENT

RETURNS DEPT
KRAMER LEVIN NAFTALIS FRANKEL
1177 AVENUE OF THE AMERICAS

NEW YORK, NY 10036



Ship Date: 27APR05
Actual Wgt: 1LB
System#: 2876429/INET2000
Account#: S *****

REF: RTS852469260416



Delivery Address Bar Code

PRIORITY OVERNIGHT

THU

Deliver By:
28APR05


FORM
0201


TRK# 7929 0871 6427

EWR A1

10036 -NY-US

Z2 NYCA




[Web](#) [Images](#) [Groups](#) [News](#) [Froogle](#) [Local](#)^{New!} [more »](#)

[Advanced Search](#)
[Preferences](#)

WebResults 1 - 10 of about 4,300,000 for **Dr. Stephen O. Friend**. (0.92 seconds)

Tip: Save time by hitting the return key instead of clicking on "search"

Poet: Stephen O Hanlon - All poems of Stephen O Hanlon... This is the website domain of **Dr Stephen O'Hanlon**. Copyright 2004. ...This Ring of Origami Art site is owned by **Dr Stephen O'Hanlon**. ...www.poemhunter.com/stephen-o-hanlon/poet-66208/ - 24k - [Cached](#) - [Similar pages](#)**The Unification of Stephen Hawking**... Four years ago, I reviewed a book called **Stephen Hawking's Universe**, ...and was told that **Dr. Hawking** (everyone with the university called him **Dr. ...**www.pacificnews.org/marko/hawking.html - 31k - [Cached](#) - [Similar pages](#)**Surgeon || Dr. Stephen Maturin**Fanlisting for **Dr. Stephen Maturin**. ... **Stephen Maturin** appears in the 20 volumes

of Patrick O'Brian's Aubrey/Maturin series, which begins with Master and ...

www.paulbettany.net/surgeon/about.html - 4k - [Cached](#) - [Similar pages](#)**The Pet Whisperer**... Blake with his new **friend** Louie ;O) **Dr. Blake's** new book is now available.... Dear Friends: I am very sad to tell you that **Dr. Stephen Blake** and his ...www.thepetwhisperer.com/ - 11k - Apr 26, 2005 - [Cached](#) - [Similar pages](#)**Dr. Steve O'Shea Interview****Dr. Steve O'Shea** Interview. What follows is TONMO.com's exclusive interviewconducted 5/10/02 with marine biologist **Dr. Steve O'Shea**. ...www.tonmo.com/osheainterview.php - 14k - Apr 26, 2005 - [Cached](#) - [Similar pages](#)**The O'Kane Chronicle**... It was later found to be the result of **Dr Bunsen Honeydew** and his ... Our **friend****Grand Moff Tarkin** is back with some more tips on cooking asparagus. ...star-www.st-and.ac.uk/~srk1/ - 11k - [Cached](#) - [Similar pages](#)**Rev. Dr. Stephen Henry OLIN**OLINotables. Rev. **Dr. Stephen Henry OLIN** ... supporting the resolution that calledupon his **friend**, Bishop James O. Andrew, to desist from the exercise of ...home.earthlink.net/~jeffreyolin/id1.html - 29k - [Cached](#) - [Similar pages](#)**15th Wisconsin, Stephen Oliver Himoe of Field & Staff, aka, Svend ...**... **Stephen O.** Himoe was an 1856 graduate of the St. Louis Medical College and... At the beginning of August, 1862, **Dr. Alfred H. Whipple** was commissioned ...www.15thwisconsin.net/15ssoh01.htm - 20k - [Cached](#) - [Similar pages](#)**Dr Stephen Juan - Odd News**The website of **Dr Stephen Juan**, author of the Odd Body and Odd Brain books. ...It is either "a **friend**" who is more competent than the child or one who is ...www.harpercollins.com.au/drstephenjuan/0312news.htm - 22k - [Cached](#) - [Similar pages](#)**Aubrey/Maturin Series by Patrick O'Brian**


[View Recent Searches](#)
[LOG](#)
match
.com


We've inspired twice as many marriages as any other site.

3 days FREE

[PEOPLE SEARCH](#) | [BUSINESS SEARCH](#) | [REVERSE PHONE](#) | [REVERSE ADDRESS](#) | [AREA CODES](#) | [ZIP CODES](#) | [ADD](#)
[INTERNATIONAL DIRECTORIES](#) | [BATCH PEOPLE SEARCHES](#)


[Get More from WhitePages!](#)

[SEARCH TOOLS FOR B](#)

We're sorry. Your search returned no results.

Please verify that your information was entered correctly, or try again with a broader range of search information.

[\[More search tips \]](#)

Search Suggestions:

• [Friend, D. MA, 01921](#)

• [Friend, D. MA](#)

• [Friend, D. U.S.](#)

Advertisement

Dr. Stephen Friend is in Our Database.

Powered by **US SEARCH**

Find Address, Phone, Background Info and More with One Click.

First Name

Dr. Stephen

Last Name

Friend

City

State

MA

ZIP

01921

Submit

» [Search by Maiden Name](#)

» [Search by Age](#)

» [Search by Social Security Number](#)

People Search

[Help](#)

First Name ☒ Begins with

Dr. Stephen

Last Name* ☐ Begins with

Friend

City or ZIP/Postal Code

01921

State or Province

Massachusetts

☐ Include surrounding area

Search

» [Automate repetitive searching](#)

» [Create Mailing Lists Online](#)

» [Find Email Addresses](#)

* required

[Americans](#)

I'm a:

Seeking a:

Age:

Zip Code:



"Meet single



Julia
22 yea
from C

» [Find a](#)

» [Find L](#)

» [Find a](#)

Join

[About MyInfo](#)

[Bookmark WhitePages.com](#)

[Tell Friends about WhiteP](#)

[HOME](#) | [FAQ](#) | [ABOUT US](#) | [ADVERTISING](#) | [AFFILIATE PROGRAM](#) | [NEWSLETTERS](#) | [CONTACT US](#) | [SITE MAP](#) | [WHITEP](#)

People
SearchBackground
CheckCriminal
RecordsReal Estate
ReportsNEW
Reverse
PhoneAll
ProductsMember
Search

Find Relatives, Friends, Classmates, A Lost Love, Anyone!

4 Easy Steps to Public Records...

- ☐ Enter search criteria & run preliminary search
- ☒ Choose the information that you're looking for
- ☐ Select the best options for your search
- ☐ Easy checkout

Choose the information that's right for you:

*GUARANTEE: NO F

Buy all People Search records for \$9.95
Get all the results listed below for just \$9.95.
The reports instantly displays all "Available"
People Search Information. Additional Reports
sold separately.

Buy a 24 Hour Pass for

Buy a 3 Day Pass for \$:

Buy a 30 Day Reunion I

or

Buy all records



We have found more than 200 records matching your search criteria. Please select or narrow your search by adding additional criteria (i.e. middle initial, state, etc)

Did you know that you can also Search by SSN or Maiden Name?

200 Preliminary Search Results for: "Stephen Friend"



What do
I do now?



Choose a result from the list, then select the kind of information you are looking to find.

Need Help?



For Expert
Assistance Call:

1-800-US-SEARCH
(1-800-877-3272)

Mon - Fri 6am - 6pm PST
Sat: 8am - 5pm PST

	Name	Age	City	State	Premiu
1	<u>STEPHEN FRIEND</u>	-	MORGANTOWN	WV	<u>Advance</u> <u>Instant</u> <u>Backgr</u>
2	<u>STEPHEN FRIEND</u>	-	MORGANTOWN	WV	<u>Advance</u> <u>Instant</u> <u>Backgr</u>
3	<u>STEPHEN FRIEND</u>	-	MORGANTOWN	WV	<u>Advance</u> <u>Instant</u> <u>Backgr</u>
4	<u>STEPHEN FRIEND</u>	-	DENVER	CO	<u>Advance</u> <u>Instant</u> <u>Backgr</u>
5	<u>STEPHEN FRIEND</u>	-	DENVER	CO	<u>Advance</u> <u>Instant</u> <u>Backgr</u>
6	<u>STEPHEN FRIEND</u>	-	WEST BOXFORD	MA	<u>Advance</u> <u>Instant</u> <u>Backgr</u>
7	<u>STEPHEN FRIEND</u>	-	SYLMAR	CA	<u>Advance</u> <u>Instant</u> <u>Backgr</u>
8	<u>STEPHEN FRIEND</u>	44	LOGAN	UT	<u>Advance</u> <u>Instant</u> <u>Backgr</u>
9	<u>STEPHEN FRIEND</u>	44	LOGAN	UT	<u>Advance</u> <u>Instant</u> <u>Backgr</u>